

**Operating and Safety Instructions****LAWN MOWER – HEAVY DUTY PETROL****USES Mowing Long Lawns – Heavy Duty****PRE CHECK**

Check fuel tank is full with fuel (91 octane)

**STARTING**

Turn fuel tap on  
Set cutting height to maximum  
Ensure gear lever is in neutral  
Pull belt release lever towards handles to disengage cutter belt  
For cold start move throttle lever to choke (7 o'clock position)  
Press starter button  
When engine starts, move throttle to 6 o'clock position  
Set height adjustment.

**OPERATION**

Select gear and pull clutch lever up.

**STOPPING**

Move throttle control to stop  
Switch off fuel.  
Lift up side chute and hose off grass under shroud around mower

**MOWERS RETURNED DIRTY WILL INCUR A CLEANING FEE.**

**SAFETY PRECAUTIONS AND EQUIPMENT**

Check the area for debris, i.e. wire, stones, wood etc  
Do not spill fuel. Check that all guards are in place.  
Do not tie up the grass discharge flap.  
Keep hands and feet clear of mower. Keep children away.  
Do not leave engine running and unattended.  
Do not clean out grass with hands while engine is running.  
Wear sturdy footwear.  
*Safety Equipment: Ear muffs, goggles, safety footwear.*

**HAZARDS**

Wire, string, wood, stones, concrete, loose blades.  
If vibration occurs stop immediately.  
Wearing inappropriate footwear.

**Personal Protective Equipment**